

SAFETY DATA SHEET



Issue Date 01-Jan-2018

Revision Date 23-Jan-2018

Version 1

1. IDENTIFICATION

Product identifier

Product Name PUMADEQ FLEX 30SL - GRAY

Other means of identification

Product Code HEPU860G

UN/ID no UN1866

Synonyms None

Recommended use of the chemical and restrictions on use

Recommended Use Industrial Coatings

Uses advised against No information available

Details of the supplier of the safety data sheet

Manufacturer Address

HENRY COMPANY

999 N. Sepulveda Blvd., Suite 800

El Segundo, CA 90245-2716

Web Site: www.henry.com www.ca.henry.com

Emergency telephone number

Company Phone Number 800-486-1278

Emergency Telephone US and Canada only (toll-free) : 3E Company - 1-866-519-4752 (access code 334832)
US/Canada, all other countries: 3E Company - +1-760-476-3962 (access code 334832)
Mexico (additional contact option): 3E Company - +52 55 41696225 (Code 334832)

2. HAZARDS IDENTIFICATION

Classification

OSHA Regulatory Status

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2
Skin sensitization	Category 1
Specific target organ toxicity (single exposure)	Category 3
Flammable liquids	Category 2

Label elements

Emergency Overview

Danger

Hazard statements

Causes skin irritation

Causes serious eye irritation

May cause an allergic skin reaction

May cause respiratory irritation

Highly flammable liquid and vapor



Appearance viscous

Physical state liquid

Odor Strong Aromatic

Precautionary Statements - Prevention

Wash face, hands and any exposed skin thoroughly after handling
Wear protective gloves/protective clothing/eye protection/face protection
Avoid breathing dust/fume/gas/mist/vapors/spray
Contaminated work clothing should not be allowed out of the workplace
Use only outdoors or in a well-ventilated area
Keep away from heat/sparks/open flames/hot surfaces. - No smoking
Keep container tightly closed
Ground/bond container and receiving equipment
Use explosion-proof electrical/ ventilating / lighting/ / equipment
Use only non-sparking tools
Take precautionary measures against static discharge
Keep cool

Precautionary Statements - Response

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
If eye irritation persists: Get medical advice/attention
If skin irritation or rash occurs: Get medical advice/attention
IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower
Wash contaminated clothing before reuse
IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing
Call a POISON CENTER or doctor/physician if you feel unwell
In case of fire: Use CO₂, dry chemical, or foam for extinction

Precautionary Statements - Storage

Store in a well-ventilated place. Keep container tightly closed
Store locked up

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Not applicable

Other Information

May be harmful if inhaled. Harmful to aquatic life with long lasting effects. Harmful to aquatic life.

Unknown acute toxicity

0% of the mixture consists of ingredient(s) of unknown toxicity

3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance

Not applicable

Mixture

Chemical Name	CAS No	Weight-%
Resin-polymer Blend *	Proprietary	40 - 70
Methyl methacrylate *	80-62-6	10 - 30
2-Ethylhexyl acrylate *	103-11-7	10 - 30
Titanium dioxide *	13463-67-7	1 - 5
Silica, amorphous, fumed, crystalline-free *	112945-52-5	1 - 5

*The exact percentage (concentration) of composition has been withheld as a trade secret.

4. FIRST AID MEASURES

Description of first aid measures

General advice	Immediate medical attention is required. In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible). If symptoms persist, call a physician.
Eye contact	Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Keep eye wide open while rinsing. If symptoms persist, call a physician.
Skin contact	Wash off immediately with soap and plenty of water. Wash contaminated clothing before reuse. If skin irritation persists, call a physician.
Inhalation	Remove to fresh air. If symptoms persist, call a physician. Artificial respiration and/or oxygen may be necessary.
Ingestion	Call a physician or poison control center immediately. Do not induce vomiting without medical advice. Rinse mouth. Never give anything by mouth to an unconscious person.
Self-protection of the first aider	Remove all sources of ignition. Use personal protective equipment as required.

Most important symptoms and effects, both acute and delayed

Symptoms	May cause redness and tearing of the eyes. May cause skin irritation. Redness. Coughing and/ or wheezing.
-----------------	---

Indication of any immediate medical attention and special treatment needed

Note to physicians	May cause sensitization in susceptible persons. Treat symptomatically.
---------------------------	--

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Dry chemical, CO₂, sand, earth, water spray or regular foam.

Unsuitable extinguishing media Do not use a solid water stream as it may scatter and spread fire.

Specific hazards arising from the chemical

In the event of fire and/or explosion do not breathe fumes. May cause sensitization in susceptible persons. Thermal decomposition can lead to release of irritating and toxic gases and vapors. Flammable.

Explosion data

Sensitivity to Mechanical Impact None.

Sensitivity to Static Discharge May be ignited by heat, sparks or flames.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Cool containers / tanks with water spray. Burning produces heavy smoke.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions Remove all sources of ignition. Evacuate personnel to safe areas. Ensure adequate ventilation, especially in confined areas. Use personal protective equipment as required. Keep people away from and upwind of spill/leak.

Environmental precautions

Environmental precautions Prevent further leakage or spillage if safe to do so. Prevent product from entering drains. Do not flush into surface water or sanitary sewer system.

Methods and material for containment and cleaning up

Methods for containment Prevent further leakage or spillage if safe to do so.

Methods for cleaning up Dam up. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Pick up and transfer to properly labeled containers.

7. HANDLING AND STORAGE**Precautions for safe handling**

Advice on safe handling Ensure adequate ventilation, especially in confined areas. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Take precautionary measures against static discharges. Use spark-proof tools and explosion-proof equipment. All equipment used when handling the product must be grounded. Use personal protective equipment as required. Avoid breathing vapors or mists.

Conditions for safe storage, including any incompatibilities

Storage Conditions Keep containers tightly closed in a cool, well-ventilated place. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Keep in properly labeled containers.

Incompatible materials Strong oxidizing agents. Strong acids. Strong bases. Amines. Halogens.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION**Control parameters****Exposure Guidelines**

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Methyl methacrylate 80-62-6	STEL: 100 ppm TWA: 50 ppm	TWA: 100 ppm TWA: 410 mg/m ³	IDLH: 1000 ppm TWA: 100 ppm TWA: 410 mg/m ³
Titanium dioxide 13463-67-7	TWA: 10 mg/m ³	TWA: 15 mg/m ³ total dust	IDLH: 5000 mg/m ³

NIOSH IDLH *Immediately Dangerous to Life or Health*

Appropriate engineering controls

Engineering Controls Minimize exposure by partial enclosure of the operation or equipment and provide extract ventilation at openings.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles).

Skin and body protection Wear protective gloves and protective clothing.

Respiratory protection If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be

provided in accordance with current local regulations.

General Hygiene Considerations When using do not eat, drink or smoke. Regular cleaning of equipment, work area and clothing is recommended.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical state	liquid	Odor	Strong Aromatic
Appearance	viscous	Odor threshold	0.34 ppm
Color	white		

<u>Property</u>	<u>Values</u>	<u>Remarks • Method</u>
pH	No information available	
Melting point / freezing point	-18 °C / 0 °F	
Boiling point / boiling range	101 °C / 213 °F	
Flash point	12 °C / 53 °F	Tag Closed Cup
Evaporation rate	3.1 (nBuOAc = 1)	
Flammability (solid, gas)	No information available	
Flammability Limit in Air		
Upper flammability limit:	12.5%	
Lower flammability limit:	2.1%	
Vapor pressure	4.7	@ 20 °C
Vapor density	No information available	
Relative density	1.36	
Water solubility	Insoluble in water	
Solubility in other solvents	No information available	
Partition coefficient	No information available	
Autoignition temperature	No information available	
Decomposition temperature	>250 C	
Kinematic viscosity	No information available	
Dynamic viscosity	No information available	
Explosive properties	Not an explosive	
Oxidizing properties	Not applicable	

Other Information

Softening point	No information available
Molecular weight	No information available
VOC Content (%)	No information available
Density	No information available
Bulk density	No information available

10. STABILITY AND REACTIVITY

Reactivity

No data available

Chemical stability

Stable under recommended storage conditions.

Possibility of Hazardous Reactions

None under normal processing.

Conditions to avoid

Heat, flames and sparks.

Incompatible materials

Strong oxidizing agents. Strong acids. Strong bases. Amines. Halogens.

Hazardous Decomposition Products

None known based on information supplied.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure**Product Information**

Inhalation	May cause irritation.
Eye contact	Irritating to eyes.
Skin contact	Irritating to skin. Repeated or prolonged skin contact may cause allergic reactions with susceptible persons.
Ingestion	Based on available data, the classification criteria are not met.

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Methyl methacrylate 80-62-6	= 7900 mg/kg (Rat) = 7872 mg/kg (Rat)	> 5 g/kg (Rabbit)	= 4632 ppm (Rat) 4 h
2-Ethylhexyl acrylate 103-11-7	= 4435 mg/kg (Rat)	= 7522 mg/kg (Rabbit)	-
Titanium dioxide 13463-67-7	> 10000 mg/kg (Rat)	-	-
Silica, amorphous, fumed, crystalline-free 112945-52-5	= 3160 mg/kg (Rat)	-	-

Information on toxicological effects

Symptoms	May cause an allergic skin reaction. May cause redness and tearing of the eyes. May cause skin irritation. Redness. Coughing and/ or wheezing.
-----------------	--

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Sensitization	Based on available data, the classification criteria are not met.
Germ cell mutagenicity	Based on available data, the classification criteria are not met.
Carcinogenicity	This product contains titanium dioxide which is classified as a possible carcinogen when present as respirable dust. This is not relevant for this product since it is a liquid. The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical Name	ACGIH	IARC	NTP	OSHA
Resin-polymer Blend	-	Group 3	-	-
Methyl methacrylate 80-62-6	-	Group 3	-	-
2-Ethylhexyl acrylate 103-11-7	-	Group 3	-	-
Titanium dioxide 13463-67-7	-	Group 2B	-	X
Silica, amorphous, fumed, crystalline-free 112945-52-5	-	Group 3	-	-

IARC (International Agency for Research on Cancer)

Not classifiable as a human carcinogen

Group 2B - Possibly Carcinogenic to Humans

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

X - Present

Reproductive toxicity	Based on available data, the classification criteria are not met.
STOT - single exposure	May cause disorder and damage to the. Respiratory system. Eyes. Skin.
STOT - repeated exposure	Based on available data, the classification criteria are not met.
Chronic toxicity	Repeated contact may cause allergic reactions in very susceptible persons. Avoid repeated exposure.
Target Organ Effects	Eyes, Respiratory system, Skin, lungs.
Aspiration hazard	Based on available data, the classification criteria are not met.

Numerical measures of toxicity - Product Information

The following values are calculated based on chapter 3.1 of the GHS document .

ATEmix (oral)	7,872.00 mg/kg
ATEmix (dermal)	5,005.00 mg/kg
ATEmix (inhalation-vapor)	4,632.00 mg/l

12. ECOLOGICAL INFORMATION

Ecotoxicity

Harmful to aquatic life with long lasting effects

0 % of the mixture consists of component(s) of unknown hazards to the aquatic environment

Chemical Name	Algae/aquatic plants	Fish	Crustacea
Methyl methacrylate 80-62-6	170: 96 h Pseudokirchneriella subcapitata mg/L EC50	243 - 275: 96 h Pimephales promelas mg/L LC50 flow-through 125.5 - 190.7: 96 h Pimephales promelas mg/L LC50 static 153.9 - 341.8: 96 h Lepomis macrochirus mg/L LC50 static 79: 96 h Oncorhynchus mykiss mg/L LC50 flow-through 79: 96 h Oncorhynchus mykiss mg/L LC50 static 170 - 206: 96 h Lepomis macrochirus mg/L LC50 flow-through 326.4 - 426.9: 96 h Poecilia reticulata mg/L LC50 static	69: 48 h Daphnia magna mg/L EC50
2-Ethylhexyl acrylate 103-11-7	44: 72 h Desmodosmus subspicatus mg/L EC50 47: 96 h Desmodosmus subspicatus mg/L EC50	23: 48 h Leuciscus idus melanotus mg/L LC50	17.45: 48 h Daphnia magna mg/L EC50

Persistence and degradability

No information available.

Bioaccumulation

Chemical Name	Partition coefficient
Methyl methacrylate 80-62-6	0.7
2-Ethylhexyl acrylate 103-11-7	4.64

Other adverse effects

No information available

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Disposal of wastes

This material, as supplied, is a hazardous waste according to federal regulations (40 CFR 261). Disposal should be in accordance with applicable regional, national and local laws and regulations.

Contaminated packaging

Do not reuse container.

US EPA Waste Number

D001 U162

Chemical Name	RCRA	RCRA - Basis for Listing	RCRA - D Series Wastes	RCRA - U Series Wastes
Methyl methacrylate 80-62-6	U162	Included in waste stream: F039	-	U162

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical Name	California Hazardous Waste Status
Methyl methacrylate	Toxic

80-62-6

Ignitable

14. TRANSPORT INFORMATION**DOT**

UN/ID no	UN1866
Proper shipping name	Resin solution
Hazard Class	3
Packing Group	II
Special Provisions	149, B52, IB2, T4, TP1, TP8
Description	UN1866, Resin solution, 3, II
Emergency Response Guide Number	127

TDG

UN/ID no	UN1866
Proper shipping name	Resin solution
Hazard Class	3
Packing Group	II
Description	UN1866, Resin solution, 3, II

IATA

UN/ID no	UN1866
Proper shipping name	Resin solution
Hazard Class	3
Packing Group	II
ERG Code	3L
Special Provisions	A3
Description	UN1866, Resin solution, 3, II

IMDG

UN/ID no	UN1866
Proper shipping name	Resin solution
Hazard Class	3
Packing Group	II
EmS-No	F-E, S-E
Description	UN1866, Resin solution, 3, II, (12°C c.c.)

15. REGULATORY INFORMATION**International Inventories**

TSCA	Complies
DSL/NDSL	Complies
EINECS/ELINCS	Complies
IECSC	Complies
KECL	Complies
PICCS	Complies
AICS	Complies

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory
DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List
EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances
ENCS - Japan Existing and New Chemical Substances
IECSC - China Inventory of Existing Chemical Substances
KECL - Korean Existing and Evaluated Chemical Substances
PICCS - Philippines Inventory of Chemicals and Chemical Substances
AICS - Australian Inventory of Chemical Substances

US Federal Regulations**SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical Name	SARA 313 - Threshold Values %
Methyl methacrylate - 80-62-6	1.0

SARA 311/312 Hazard Categories

Acute health hazard	Yes
Chronic Health Hazard	No
Fire hazard	Yes
Sudden release of pressure hazard	No
Reactive Hazard	No

CWA (Clean Water Act)

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Methyl methacrylate 80-62-6	1000 lb	-	-	X

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical Name	Hazardous Substances RQs	CERCLA/SARA RQ	Reportable Quantity (RQ)
Methyl methacrylate 80-62-6	1000 lb	-	RQ 1000 lb final RQ RQ 454 kg final RQ

US State Regulations**California Proposition 65**

This product contains the following Proposition 65 chemicals

Chemical Name	California Proposition 65
Titanium dioxide - 13463-67-7	Carcinogen

U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania
Methyl methacrylate 80-62-6	X	X	X
2-Ethylhexyl acrylate 103-11-7	X	X	X
Titanium dioxide 13463-67-7	X	X	X

U.S. EPA Label Information

EPA Pesticide Registration Number Not applicable

16. OTHER INFORMATION, INCLUDING DATE OF PREPARATION OF THE LAST REVISION

NFPA	Health hazards 2	Flammability 3	Instability 0	Physical and Chemical Properties -
HMIS	Health hazards 2	Flammability 3	Physical hazards 0	Personal protection X

Issue Date 01-Jan-2018

Revision Date 23-Jan-2018

Revision Note

No information available

Disclaimer

The information provided in this Material Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet