



TECHNICAL DATA SHEET
Blueskin PreSeal™ Tape 120V
Reinforced Acrylic Detailing Tape

Physical property	Typical value	Test method
Color	White with non-woven facer	-
Minimum Application Temperature	20°F (-7°C)	-
Service Temperature	-22 °F (-30 °C) to 110 °F (37 °C)	-

Description

Henry® Blueskin PreSeal™ Tape 120V is a non-woven/fleece tape with waterproof acrylic adhesive for detailing and seaming the Blueskin 320 and Henry Blueskin PreSeal 435 pre-applied waterproofing membranes.

Features and benefits

- Fiberglass reinforced
- Ultra-tack acrylic adhesive
- Fully adheres detail areas to prevent water ingress

Usage

Designed for commercial construction applications, **Blueskin PreSeal Tape 120V** may be applied on both horizontal and vertical waterproofing applications and is also used in detailing the **Blueskin PreSeal 320** and **Blueskin PreSeal 435 pre-applied waterproofing membrane** in corners, edges, penetrations, etc. The non-woven side should be applied facing the concrete pour.

Application

Surface Preparation: Clean substrates to receive **Blueskin PreSeal Tape 120V** and remove any dirt, dust or moisture. Clean the surface of penetrations or protrusions with a wire brush to remove dirt, dust, rust and loose particles.

Unroll the tape, remove the release liner, and adhere the exposed pressure sensitive adhesive surface to the membrane or penetration. The reinforced surface of the tape should face toward the concrete to be cast onto the tape. The use of rollers is required to maximize adhesion.

Refer to Blueskin PreSeal Pre-Applied Waterproofing System Installation Manual for detailed application information.

Limitations: **Blueskin PreSeal Tape 120V** is designed for a maximum exposure of up to 120 days, but is not designed for permanent exposure to ultra-violet light and should be covered as soon as practical after application.

Product size/packaging

Roll Size 4.75 in. x 98 ft. (120 mm x 30 m)
8 Rolls/Box

Storage

Shelf Life: One year from date of manufacture.

The **Blueskin PreSeal Tape 120V** should be stored dry and protected from sunlight, at 41 °F (5 °C) to 77 °F (25 °C).

For more information, visit www.henry.com or for technical assistance call us at 800-486-1278. For more information on the Henry® product warranty and liability disclaimer please visit www.henry.com/warranty. Refer to the Safety Data Sheet prior to using this product. The Safety Data Sheet is available at www.henry.com or by emailing Henry® Product Support at productsupport@henry.com or by calling 800-486-1278.

Henry and Blueskin are registered trademarks of Henry Company. PreSeal or Blueskin PreSeal are trademarks of Henry Company. Max Frank is a registered trademark of Max Frank GmbH & Co.

Blueskin® PreSeal Tape 120V

The technical and application information herein is based on the present state of our best scientific and practical knowledge. As the information herein is of a general nature, no assumption can be made as to a product's suitability for a particular use or application and no warranty as to its accuracy, reliability or completeness either expressed or implied is given other than those required by law. The user is responsible for checking the suitability of products for their intended use. Henry® Company data sheets are updated on a regular basis; it is the user's responsibility to obtain and to confirm the most recent version. Information contained in this data sheet may change without notice.

In partnership with

