



### Physical Properties

<b>Appearance</b> Black fluid	<b>Maximum VOC</b> 350 g/l	<b>Specific Gravity @ 77° F (25°C)</b> 0.9
<b>Color</b> Black	<b>Solids By Weight</b> 56.2%	<b>Weight Per Gallon</b> 7.2 - 7.7 lbs.
<b>Flash Point</b> 105°F		

### Description

**HE0400 - Henry #400 GEL SEAL CANISTER G RADE RUST PREVENTATIVE COATIN** is a thixotropic material formulated with selected asphalts and mineral spirits for use as a protective coating for underbody areas of cars, trucks and trailers. After application, the film dries to a black, firm, resilient, non-tacky finish. It demonstrates excellent abrasion resistance. It will not crack or peel. **HE0400 - Henry #400 GEL SEAL CANISTER G RADE RUST PREVENTATIVE COATIN** provides corrosion protection as well as sound deadening and insulating characteristics.

**FOR METAL SUBSTRATES ONLY.**

### Usage

**HE0400 - Henry #400 GEL SEAL CANISTER G RADE RUST PREVENTATIVE COATIN** is primarily intended for automotive and trailer underbody protection. Other uses include undersides of shipping containers and any metal surfaces requiring sound deadening and/or abrasion-corrosion protection.

### Coverage

1 gallon/100 sq. ft.

### Surface Preparation

All areas to be coated should be clean and free of any dirt and caked-on material.

### Application

Recommended application is through syphon type spray systems. Air pressure should be 90 - 100 psi, depending on temperature. During application to the underbody of cars, **DO NOT SPRAY** catalytic converter, transmission, heat shields, drive shaft, exhaust manifold, brake drums, oil pan or brake discs. Additional shaking may be required if stored for a prolonged period of time.

**NOTE:** This product is carefully manufactured in specially designed equipment and every batch is triple pressure-screened for positive elimination of foreign matter, insuring against gun clogs and pump troubles.

### Precautions

Do not heat container or store at temperatures greater than 110°F. When transporting this product, be sure the container is secured and the lid is tight. Do not allow container to tumble as this may loosen the lid and allow leakage to occur.

### Cleanup

All equipment can be cleaned with kerosene or mineral spirits. Observe all label precautions. Use care when handling solvents. Clean hands with a waterless hand cleaner.

### Caution

**WARNING! COMBUSTIBLE!** Contains petroleum distillate. Keep away from heat and flame. Do not heat container or store at

temperatures greater the 110° F. **CLOSE AIR INTAKES** on roof until solvents dissipate. Contains volatile solvents that might contaminate potable water. Close container after use. **DANGER! HARMFUL OR FATAL IF SWALLOWED! If swallowed**, do not induce vomiting. CALL A PHYSICIAN IMMEDIATELY! Use protective measures to avoid contact with eyes and skin. **In case of eye contact**, open eyelids wide and flush immediately with plenty of water for at least 15 minutes. **In case of accidental injection** by power spray equipment, GET MEDICAL ATTENTION IMMEDIATELY! **USE ONLY WITH ADEQUATE VENTILATION!** If you experience eye watering, headaches, or dizziness, leave area immediately or increase fresh air or wear respiratory protection (**NIOSH/MSHA TC 23C** or equivalent). Repeated and prolonged occupational overexposure to solvent vapor may cause permanent brain and nervous system damage, and may cause liver or kidney damage.

**KEEP OUT OF REACH OF CHILDREN!**

**FOR EXTERIOR USE ONLY.**

**WARNING:** This product contains detectable amounts of chemicals known to the State of California to cause cancer, or birth defects, or other reproductive harm.

**EMPLOYERS** should obtain a copy of the **Material Safety Data Sheet (MSDS)** from your supplier or directly from Henry at the toll free number or website below.

### Product Sizes

55 GAL/205 L (8.3 lb)

BULK (GALLONS) (8.3 lb)

55 GAL (blk un openhead drum)

### Limited Warranty

We, the manufacturer, warrant only that this product is free of defects, since many factors which affect the results obtained from this product - such as weather, workmanship, equipment utilized and prior condition of the substrate - are all beyond our control. We will replace at no charge any product proved to be defective within 12 months of purchase, provided it has been applied in accordance with our written directions for uses we recommended as suitable for this product. Proof of purchase must be provided. **DISCLAIMER OF WARRANTIES AND LIMITATION OF LIABILITY: THIS LIMITED WARRANTY IS IN LIEU OF ANY OTHER WARRANTIES EXPRESS OR IMPLIED INCLUDING BUT NOT LIMITED TO ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FOR A PARTICULAR PURPOSE. MANUFACTURER SHALL HAVE NO LIABILITY OF ANY KIND BEYOND PRODUCT REPLACEMENT, INCLUDING FOR CONSEQUENTIAL OR INCIDENTAL DAMAGES RESULTING FROM ANY DEFECTS OR ANY DELAYS CAUSED BY REPLACEMENT OR OTHERWISE. THIS LIMITED WARRANTY PROVIDES THE PURCHASER'S EXCLUSIVE REMEDY FOR ANY DEFECT IN THE PRODUCT.**