



#1 CHOICE OF PROFESSIONALS®

HE094 – CALSEAL CRACK FILLER

Physical Properties

<b>Appearance</b> Heavy Liquid	<b>Flash Point</b> >390°F	<b>Resiliency</b> 40-68% @ 77°F (ASTM D-5329)
<b>Color</b> Black	<b>Flow @ 140°F</b> 0-3 mm (ASTM D-5329)	<b>Softening Point</b> 195° - 205°F
<b>Cone Pen Viscosity</b> 20-50 dmm (ASTM D-5329)	<b>Freezability</b> Will not freeze	<b>Specific Gravity @ 77°F</b> 1.17
<b>Ductility @ 77°F, 5cm/min</b> 30-38 cm (ASTM D-113)	<b>Maximum VOC</b> 0 Calculated	<b>Weight Per Gallon</b> 9.7 – 9.8 lbs.

APPROVALS AND CERTIFICATIONS

Meets Type II and Type III under Caltrans specification NSSP 37-400

DESCRIPTION

HE094 – CALSEAL CRACK FILLER is a mixture of paving asphalt and ground rubber or ground rubber and polymer which conforms to the above requirements.

USAGE

HE094 – CALSEAL CRACK FILLER is used for sealing cracks in asphaltic and concrete highways, city streets and rural roadways.

PRODUCT SIZE

35 LB.

SURFACE PREPARATION

Surface must be dry and free from all loose material, dirt and dust. Any weeds or plant matter should be removed and the area sprayed with herbicide. Routing is optional.

APPLICATION

HE094 – CALSEAL CRACK FILLER can be melted and applied to cracks and joints at temperatures below 400°F. When heated, product will readily penetrate cracks 1/4" wide or larger. Cracks can be filled flush or may be over-filled and squeegeed.

HE094 – CALSEAL CRACK FILLER can be applied using a pressure feed wand system or with a pour pot.

PRECAUTIONS

Do not allow material to exceed 400°F.

## CLEANUP

---

Asphalt can be cleaned with mineral spirits. Otherwise it can be cleaned with a waterless hand cleaner.

## CAUTION

---

Close container after each use. DO NOT TAKE INTERNALLY! Use protective measures to avoid contact with eyes and skin. **If swallowed, CALL PHYSICIAN IMMEDIATELY!** In case of accidental injection by power spray equipment, GET MEDICAL ATTENTION IMMEDIATELY! Dispose of container and unused contents in accordance with Local, State and Federal regulations.

**KEEP OUT OF REACH OF CHILDREN!**

**KEEP FROM FREEZING!**

**Warning:** This product contains detectable amounts of chemicals known to the State of California to cause cancer, or birth defects or other reproductive harm.

**Employers** Should obtain a copy of the **Material Safety Data Sheet (MSDS)** from your supplier or directly from Henry at the toll free number or website below.

## Limited Warranty

---

We, the manufacturer, warrant only that this product is free of defects, since many factors which affect the results obtained from this product - such as weather, workmanship, equipment utilized and prior condition of the substrate - are all beyond our control. We will replace at no charge any product proved to be defective within 12 months of purchase, provided it has been applied in accordance with our written directions for uses we recommended as suitable for this product. Proof of purchase must be provided. DISCLAIMER OF WARRANTIES AND LIMITATION OF LIABILITY: THIS LIMITED WARRANTY IS IN LIEU OF ANY OTHER WARRANTIES EXPRESS OR IMPLIED INCLUDING BUT NOT LIMITED TO ANY IMPLIED WARRANTY OF MERCHANTABILITY OR OF FITNESS FOR A PARTICULAR PURPOSE. MANUFACTURER SHALL HAVE NO LIABILITY OF ANY KIND BEYOND PRODUCT REPLACEMENT, INCLUDING FOR CONSEQUENTIAL OR INCIDENTAL DAMAGES RESULTING FROM ANY DEFECTS OR ANY DELAYS CAUSED BY REPLACEMENT OR OTHERWISE. THIS LIMITED WARRANTY PROVIDES THE PURCHASER'S EXCLUSIVE REMEDY FOR ANY DEFECT IN THE PRODUCT.