



Last Rev Date: 02/25/2014

Physical Properties

Appearance Roll mesh fabric	Flash Point >212°F	Mesh Size 20 X 10
Color Black	Maximum VOC 0 calculated	Tensile Strength Film (Initial) 75 lbs/in

Approvals and Certifications

Complies with ASTM D-1668, Type I.

Description

HE181 - ROOF REPAIR FABRIC ASPHALT SATURATED is woven fabric 20 X 10 mesh, made of yarns of inert, flexible filaments of pure glass saturated with asphalt. It has a tensile strength of 75 lb/in., stability and durability, is acid and heat resistant, and will not rot or decay.

Usage

HE181 - ROOF REPAIR FABRIC ASPHALT SATURATED is designed to reinforce **Henry #204 Plastic Roof Cement**, **#209 Extreme Wet Patch Roof Leak Repair**, **#505 FlashMaster™ Flashing Cement**, **#208R Rubberized Wet Patch Roof Leak Repair**, and **#208 Wet Patch Roof Leak Repair**, **#906 FlashMaster™ Plus Wet or Dry Flashing Cement** and coatings when used in roof repair work, for flashings, and for sealing seams in metal and composition roofs. It is also used in below-grade waterproofing applications, tank lining systems, and for waterproofing planter boxes.

Surface Preparation

Be sure the roof surface is clean and dry before applying roof cement.

Application

Apply roof cement approximately 1/8" thick, or coating approximately 1/16" thick or as specified. Embed **HE181 - ROOF REPAIR FABRIC ASPHALT SATURATED** smoothly without wrinkles or buckles. Top coat fabric with roof cement or coating of the same thickness as the embedding coat, or as specified, making sure the glass is entirely covered.

Cleanup

Asphalt can be removed by use of mineral spirits, paint remover, or kerosene. Use caution when handling solvents.

Caution

WARNING: This product contains detectable amounts of chemicals known to the State of California to cause cancer, or birth defects, or other reproductive harm.

Employers should obtain a copy of the **Material Safety Data Sheet (MSDS)** from your supplier or directly from Henry at the toll free number or website below.

Product Sizes

4IN X 150FT ROLL (1 lb)

6IN X 150FT ROLL (1.5 lb)

36IN X 150FT ROLL (9 lb)

Limited Warranty

We, the manufacturer, warrant only that this product is free of defects, since many factors which affect the results obtained from this product - such as weather, workmanship, equipment utilized and prior condition of the substrate - are all beyond our control. We will replace at no charge any product proved to be defective within 12 months of purchase, provided it has been applied in accordance with our written directions for uses we recommended as suitable for this product. Proof of purchase must be provided. **DISCLAIMER OF WARRANTIES AND LIMITATION OF LIABILITY: THIS LIMITED WARRANTY IS IN LIEU OF ANY OTHER WARRANTIES EXPRESS OR IMPLIED INCLUDING BUT NOT LIMITED TO ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FOR A PARTICULAR PURPOSE. MANUFACTURER SHALL HAVE NO LIABILITY OF ANY KIND BEYOND PRODUCT REPLACEMENT, INCLUDING FOR CONSEQUENTIAL OR INCIDENTAL DAMAGES RESULTING FROM ANY DEFECTS OR ANY DELAYS CAUSED BY REPLACEMENT OR OTHERWISE. THIS LIMITED WARRANTY PROVIDES THE PURCHASER'S EXCLUSIVE REMEDY FOR ANY DEFECT IN THE PRODUCT.**