



Physical Properties

Appearance Fabric	Flash Point 212°F	Maximum VOS 0 calculated
Color Black	Maximum VOC 0 calculated	

Approvals and Certifications

Manufactured to exceed the requirements of ASTM D-3909 and Federal Specification SS-R-602D, Class 3.

UL listed for Class A and B fire rated roof coverings.

Consult Henry Representative for specific assembly ratings and requirements.

See Henry Specification Manual for detailed Roofing, Re-roofing, and Roof Maintenance & Restoration.



Description

HE606 - SBS 80# UNDERLAYMENT is a fire rated cap sheet manufactured to meet the needs of a quality built-up roofing system especially formulated for cold weather application. This cap sheet can be applied with hot mopping asphalt or cold process procedures.

This product is manufactured on tested fiberglass mat. The glass mat is impregnated and coated with a lightly modified rubberized asphalt, filled with fire retardant fillers, and surfaced with mineral/ceramic color coated granules for ultraviolet protection and weatherability.

Usage

HE606 - SBS 80# UNDERLAYMENT is used as a Fire Rated Cap Sheet to meet the needs of a quality built-up roof.

Coverage

SIZES:

- Roll length: Approximately 33'
- Roll width: Approximately 39.4"
- Roll weight: Approximately 78 lbs
- Rolls Per Pallet: 25

Surface Preparation

The substrate surface must be smooth enough to prevent puncturing of the buffer layer under normal roof traffic.

Application

Application details as specified for each project must be followed as they will vary to suit project conditions. Cut the rolls into lengths suitable for application and laid flat to eliminate curl. Unless otherwise specified, this buffer layer is laid mineral side down with 2" side laps and 4" end laps and nailed to nailable decks or spot-adhered, cold or hot method, to non-nailable decks and certain insulation boards.

Cleanup

Asphalt can be removed by use of mineral spirits, paint remover, or kerosene. Use caution when handling solvents.

Caution

WARNING: This product contains detectable amounts of chemicals known to the State of California to cause cancer, or birth defects or other reproductive harm.

EMPLOYERS should obtain a copy of the **Material Safety Data Sheet (MSDS)** from your supplier or directly from Henry at the toll free number or website below.

Product Sizes

39 3/8IN X 33FT ROLL (78 lb)

Limited Warranty

We, the manufacturer, warrant only that this product is free of defects, since many factors which affect the results obtained from this product - such as weather, workmanship, equipment utilized and prior condition of the substrate - are all beyond our control. We will replace at no charge any product proved to be defective within 12 months of purchase, provided it has been applied in accordance with our written directions for uses we recommended as suitable for this product. Proof of purchase must be provided. **DISCLAIMER OF WARRANTIES AND LIMITATION OF LIABILITY: THIS LIMITED WARRANTY IS IN LIEU OF ANY OTHER WARRANTIES EXPRESS OR IMPLIED INCLUDING BUT NOT LIMITED TO ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FOR A PARTICULAR PURPOSE. MANUFACTURER SHALL HAVE NO LIABILITY OF ANY KIND BEYOND PRODUCT REPLACEMENT, INCLUDING FOR CONSEQUENTIAL OR INCIDENTAL DAMAGES RESULTING FROM ANY DEFECTS OR ANY DELAYS CAUSED BY REPLACEMENT OR OTHERWISE. THIS LIMITED WARRANTY PROVIDES THE PURCHASER'S EXCLUSIVE REMEDY FOR ANY DEFECT IN THE PRODUCT.**