



FLASHING INSTALLED AFTER WRB
 REVERSE LAP

AIR-BLOC 31MR
 LAP AIR BARRIER
 1" ONTO FLASHING

OPTIONAL INSULATION

SET TERMINATION BAR
 IN A BED OF
HENRY 925 BES SEALANT

BLUESKIN TWF

HENRY BELOW GRADE
WATERPROOFING
 (CONTACT HENRY FOR
 PROJECT SPECIFIC
 RECOMMENDATIONS)

NOTES:

1. DETAIL SHOWS **AIR-BLOC 31MR FLUID APPLIED VAPOR PERMEABLE AIR BARRIER**. SUBSTRATE SHOWN IS FOR REFERENCE ONLY. ACCEPTABLE SUBSTRATES INCLUDE PLYWOOD, OSB, CONCRETE, CMU, METAL, AND EXTERIOR GRADE SHEATHING.
2. INSTALL **AIR-BLOC 31MR** TO ACHIEVE A CONTINUOUS WATER-RESISTIVE BARRIER (WRB). OPTIONAL VAPOR BARRIER NOT SHOWN FOR CLARITY. REFER TO LOCAL CODE ORDINANCES FOR INSULATION AND VAPOR BARRIER REQUIREMENTS.
3. REFER TO PRODUCT SPECIFIC TECHNICAL DATA SHEET (TDS) AND **AIR-BLOC 31MR** GUIDE SPECIFICATION FOR INSTALLATION PROCEDURES.

Henry[®]

999 N. Pacific Coast Highway, Suite 800
 El Segundo, CA 90245
 800-486-1278 • www.henry.com

MANUFACTURER GUIDE DETAILS ARE FOR REFERENCE ONLY. HENRY DOES NOT ASSUME RESPONSIBILITY FOR ERRORS OR DEVIATIONS IN DESIGN OR ENGINEERING. PROJECT SPECIFIC VERIFICATION IS RECOMMENDED PRIOR TO INSTALLATION.

AIR-BLOC 31MR FLUID APPLIED VAPOR PERMEABLE AIR BARRIER

WALL FOUNDATION

**EXTERIOR WALL AND FOUNDATION TRANSITION
 SLAB BELOW GRADE WITH MASONRY LEDGE**

SCALE: N.T.S.

03-05-2020

AB31MR-1A