



NOTES:

1. DETAIL SHOWS HENRY PRE-APPLIED WATERPROOFING SYSTEM FOR APPLICATIONS USING HENRY **BLUESKIN PRESEAL 435**. REFER TO DETAIL BSPS-0A1 FOR APPLICATIONS USING **BLUESKIN PRESEAL 320**. SUBSTRATE SHOWN IS FOR REFERENCE ONLY.
2. APPLICATIONS USING **HYDRO-FLEX WATERSTOP**: 2" MINIMUM CONCRETE COVERAGE ON ALL SIDES.
3. REFER TO PRODUCT SPECIFIC TECHNICAL DATA SHEET (TDS) AND GUIDE SPECIFICATION FOR INSTALLATION PROCEDURES.

MANUFACTURER GUIDE DETAILS ARE FOR REFERENCE ONLY. HENRY DOES NOT ASSUME RESPONSIBILITY FOR ERRORS OR DEVIATIONS IN DESIGN OR ENGINEERING. PROJECT SPECIFIC VERIFICATION IS RECOMMENDED PRIOR TO INSTALLATION.

HENRY PRE-APPLIED WATERPROOFING SYSTEM

ASSEMBLY AT UNDER SLAB

BLUESKIN PRESEAL 435
SINGLE REINFORCED SLAB ON COMPACTED EARTH

SCALE: N.T.S.

11-20-2020

BSPS-0A2

Henry[®]

999 N. Pacific Coast Highway, Suite 800
El Segundo, CA 90245
800-486-1278 • www.henry.com