

## NOTES:

- DETAIL SHOWS BLUESKIN SA SELF-ADHERED WATER RESISTIVE AIR BARRIER. SUBSTRATE SHOWN IS FOR REFERENCE ONLY. ACCEPTABLE SUBSTRATES INCLUDE PLYWOOD, OSB, CONCRETE, CMU, METAL, AND EXTERIOR GRADE SHEATHING.
- SELF-ADHERED MEMBRANE PRIMER NOT SHOWN FOR CLARITY.
- INSTALL BLUESKIN SA TO ACHIEVE A CONTINUOUS WATER-RESISTIVE BARRIER (WRB). REFER TO LOCAL CODE ORDINANCES FOR INSULATION AND VAPOR BARRIER REQUIREMENTS.
- 4. REFER TO PRODUCT SPECIFIC TECHNICAL DATA SHEET (TDS) AND **BLUESKIN SA** GUIDE SPECIFICATION FOR INSTALLATION PROCEDURES.



DEVIATIONS IN DESIGN OR ENGINEERING. PROJECT SPECIFIC VERIFICATION IS RECOMMENDED PRIOR TO INSTALLATION.

MANUFACTURER GUIDE DETAILS ARE FOR REFERENCE ONLY. HENRY DOES NOT ASSUME RESPONSIBILITY FOR ERRORS OR

## **BLUESKIN SA SELF-ADHERED WATER RESISTIVE AIR BARRIER**

## WALL FOUNDATION

EXTERIOR WALL AND FOUNDATION TRANSITION SLAB ON GRADE WITH MASONRY LEDGE

SCALE: N.T.S.

06-30-2020

BSSA-1B

999 N. Pacific Coast Highway, Suite 800 El Segundo, CA 90245 800-486-1278 • www.henry.com