



**NOTES:**

1. DETAIL SHOWS **BLUESKIN® VP100** ASSEMBLY INSTALLED OVER EXTERIOR GRADE SHEATHING. ACCEPTABLE SUBSTRATES INCLUDE PLYWOOD, OSB, CONCRETE, GYPSUM BOARD AND CONCRETE BLOCK.
2. INSULATION, CLADDING, AND OPTIONAL VAPOR BARRIER NOT SHOWN FOR CLARITY.
3. REFER TO **BLUESKIN® VP100** GUIDE SPECIFICATION FOR RECOMMENDED INSTALLATION PROCEDURES.

**Henry**®

999 Sepulveda Blvd., Suite 800  
 El Segundo, CA 90245  
 800-486-1278 • www.henry.com

MANUFACTURER GUIDE DETAILS ARE FOR REFERENCE ONLY. HENRY® DOES NOT ASSUME RESPONSIBILITY FOR ERRORS OR DEVIATIONS IN DESIGN OR ENGINEERING. PROJECT SPECIFIC VERIFICATION IS RECOMMENDED PRIOR TO INSTALLATION.

**BLUESKIN® VP100 SELF-ADHERED WATER RESISTIVE AIR BARRIER**

**PIPE PENETRATION**

SUBSTRATE GAPS UP TO 3/4" WIDE GAP MAXIMUM  
**BLUESKIN® FLEXIBLE BUTYL FLASH**

SCALE: N.T.S.

03-20-2018

**BSVP100-2D**