



NOTES:

1. DETAIL SHOWS **BLUESKIN® VP160** ASSEMBLY INSTALLED OVER EXTERIOR GRADE SHEATHING. ACCEPTABLE SUBSTRATES INCLUDE PLYWOOD, OSB, CONCRETE, GYPSUM BOARD AND CONCRETE BLOCK.
2. PRIME RAW EDGES OF EXTERIOR GYPSUM SHEATHING WHERE **AIR-BLOC® LF** IS ANTICIPATED TO LAP ONTO CUT AND EXPOSED GYPSUM CORE AT PIPE PENETRATION HOLE. RECOMMENDED PRIMER/ADHESIVE INCLUDE: **BLUESKIN® SPRAY PREP**.
3. INSULATION, CLADDING AND OPTIONAL VAPOR BARRIER NOT SHOWN FOR CLARITY.
4. REFER TO **BLUESKIN® VP160** INSTALLATION MANUAL FOR RECOMMENDED INSTALLATION PROCEDURES.

Henry®

999 Sepulveda Blvd., Suite 800
 El Segundo, CA 90245
 800-486-1278 • www.henry.com

MANUFACTURER GUIDE DETAILS ARE FOR REFERENCE ONLY. HENRY® DOES NOT ASSUME RESPONSIBILITY FOR ERRORS OR DEVIATIONS IN DESIGN OR ENGINEERING. PROJECT SPECIFIC VERIFICATION IS RECOMMENDED PRIOR TO INSTALLATION.

BLUESKIN® VP160 SELF-ADHERED WATER RESISTIVE AIR BARRIER

PIPE PENETRATION

SUBSTRATE GAPS UP TO 1/2" WIDE GAP MAXIMUM
AIR-BLOC® LF LIQUID-APPLIED FLASHING

SCALE: N.T.S.

06-20-2017

BSVP160-2B