

BLUESKIN® BUTYL FLASH, BLUESKIN® SA, BLUESKIN® SALT OR METAL CLAD®

EXTEND FLASHING 3" MIN

BLUESKIN® VP160

CLADDING AND INSULATION AS SPECIFIED

BLUESKIN® VP160, BLUESKIN® BUTYL FLASH, BLUESKIN® SA, BLUESKIN® SALT OR METAL CLAD®

LAP FLASHING 3" MIN ONTO EACH SIDE OF SUBSTRATE AT DISSIMILAR MATERIAL TRANSITIONS

2" OVERLAP WHERE **BLUESKIN® VP160** LAPS ONTO FLASHING

REFER TO HENRY® DETAIL BSVP160-8B OR BSVP160-8C SUBSTRATE GAPS FOR DEFLECTION JOINT RECOMMENDATIONS

BLUESKIN® VP160, BLUESKIN® BUTYL FLASH, BLUESKIN® SA, BLUESKIN® SALT OR METAL CLAD®

BLUESKIN® BUTYL FLASH, BLUESKIN® SA, BLUESKIN® SALT OR METAL CLAD®

CONTACT HENRY® FOR RECOMMENDATIONS WHERE THE ROOFING ASSEMBLY TRANSITIONS ONTO THE AIR BARRIER.

BLUESKIN® BUTYL FLASH, BLUESKIN® SA, BLUESKIN® SALT OR METAL CLAD®

OPTIONAL AIR/VAPOR BARRIER

212 SEALANT
(TROWEL SEALANT UNTIL MEMBRANE EDGE IS FULLY COATED TO PROMOTE WATER SHEDDING)

NOTES:

1. DETAIL SHOWS **BLUESKIN® VP160** ASSEMBLY INSTALLED OVER EXTERIOR GRADE SHEATHING. ACCEPTABLE SUBSTRATES INCLUDE PLYWOOD, OSB, CONCRETE, GYPSUM BOARD AND CONCRETE BLOCK.
2. PRIME **BLUESKIN® VP160** WHERE **BLUESKIN® SA, BLUESKIN® SALT OR METAL CLAD®** LAP ONTO **BLUESKIN® VP160**. RECOMMENDED PRIMERS/ADHESIVES INCLUDE: **BLUESKIN® LVC ADHESIVE, AQUATAC™ PRIMER OR BLUESKIN® ADHESIVE.**
3. INSTALL THE **BLUESKIN® VP160** ASSEMBLY TO PROVIDE A CONTINUOUS AIR AND WATER BARRIER.
4. REFER TO **BLUESKIN® VP160** INSTALLATION MANUAL FOR RECOMMENDED INSTALLATION PROCEDURES.

Henry®

999 Sepulveda Blvd., Suite 800
El Segundo, CA 90245
800-486-1278 • www.henry.com

MANUFACTURER GUIDE DETAILS ARE FOR REFERENCE ONLY. HENRY® DOES NOT ASSUME RESPONSIBILITY FOR ERRORS OR DEVIATIONS IN DESIGN OR ENGINEERING. PROJECT SPECIFIC VERIFICATION IS RECOMMENDED PRIOR TO INSTALLATION.

BLUESKIN® VP160 SELF-ADHERED WATER RESISTIVE AIR BARRIER

PARAPET TRANSITION

ROOFING ASSEMBLY WRAPPING
OVER TOP OF PARAPET

SCALE: N.T.S.

06-20-2017

BSVP160-9B1