



EXTERIOR GRADE SHEATHING
(ACCEPTABLE SUBSTRATES INCLUDE
GYPSUM BOARD, PLYWOOD, OSB,
CONCRETE AND CONCRETE BLOCK)

NO SUPPLEMENTAL DETAILING
REQUIRED FOR SUBSTRATE GAPS UP
TO 1/2" WIDE WHERE **BLUESKIN® VP160**
IS INSTALLED CONTINUOUSLY AND
MEMBRANE SEAMS EXTEND A MINIMUM
OF 3" BEYOND SUBSTRATE GAPS.

BLUESKIN® VP160

BLUESKIN® TWF

FOUNDATION AS SPECIFIED

CONTACT HENRY® FOR
RECOMMENDATIONS WHERE THE AIR
BARRIER TRANSITIONS ONTO THE
WATERPROOFING ASSEMBLY

NOTES:

1. DETAIL SHOWS **BLUESKIN® VP160** ASSEMBLY INSTALLED OVER EXTERIOR GRADE SHEATHING. ACCEPTABLE SUBSTRATES INCLUDE PLYWOOD, OSB, CONCRETE, GYPSUM BOARD AND CONCRETE BLOCK.
2. HENRY® **BLUESKIN® VP160** MAY BE INSTALLED VERTICALLY OR HORIZONTALLY.
3. WHERE ENHANCED ADHESION IS DESIRED PRIME **BLUESKIN® VP160** WHERE **BLUESKIN® VP160** LAPS ONTO **BLUESKIN® VP160**. RECOMMENDED PRIMERS/ADHESIVES INCLUDE: **BLUESKIN® LVC ADHESIVE**, **AQUATAC™ PRIMER** OR **BLUESKIN® ADHESIVE**.
4. INSTALL THE **BLUESKIN® VP160** IN A SHINGLE FASHION TO PROVIDE A CONTINUOUS AIR AND WATER BARRIER.
5. REFER TO **BLUESKIN® VP160** INSTALLATION MANUAL FOR RECOMMENDED INSTALLATION PROCEDURES.

Henry®

999 Sepulveda Blvd., Suite 800
El Segundo, CA 90245
800-486-1278 • www.henry.com

MANUFACTURER GUIDE DETAILS ARE FOR REFERENCE ONLY. HENRY® DOES NOT ASSUME RESPONSIBILITY FOR ERRORS OR DEVIATIONS IN DESIGN OR ENGINEERING. PROJECT SPECIFIC VERIFICATION IS RECOMMENDED PRIOR TO INSTALLATION.

BLUESKIN® VP160 SELF-ADHERED WATER RESISTIVE AIR BARRIER

**HORIZONTAL
INSTALLATIONS**

SCALE: N.T.S.

06-20-2017

BSVP160-3D2