



**NOTES:**

1. DETAIL SHOWS HENRY **DUNDEQ** SYSTEM FULL SEED AND LOCK TRAFFIC COATING. SUBSTRATE SHOWN IS FOR REFERENCE ONLY. REFER TO PRODUCT SPECIFIC TECHNICAL DATA SHEET FOR AUTHORIZED SUBSTRATES.
2. HENRY **DUNDEQ** SYSTEM STANDARD PRIMERS: **HENRY LV PRIMER** AND **HENRY LVXL PRIMER**.
3. OTHER RECOMMENDED PRIMERS INCLUDE: **HENRY ST PRIMER** AND AGGREGATE, **HENRY STXL PRIMER** AND AGGREGATE, **PUMADEC PRIMER 20** AND AGGREGATE OR **HENRY GC EPOXY PRIMER**. REFER TO THE **DUNDEQ** SYSTEM SUBSTRATE PRIMER GUIDELINES TECH-TALK BULLETIN FOR APPLICATION RECOMMENDATIONS.
4. FULLY BROADCAST, TO REJECTION, DRY SILICA SAND INTO WET WEAR COAT (SIEVE SIZE: #20-50, #12 SILICA OR NJ0-NJ00).
5. REMOVE EXCESS PRIMER FROM GAP PRIOR TO APPLYING **HENRY DUNDEQ GP FLEXCOAT**.
6. PREPARE AND PRIME VERTICAL SUBSTRATES A MINIMUM 2" BEYOND **DUNDEQ** SYSTEM APPLICATION IN ACCORDANCE WITH HENRY **DUNDEQ** SYSTEM SUBSTRATE PREPARATION GUIDELINES.
7. DO NOT INSTALL **DUNDEQ** SYSTEM BEYOND PRIMED SURFACES.
8. REFER TO **DUNDEQ** SYSTEM GUIDE SPECIFICATION AND **DUNDEQ** SYSTEM DETAILS FOR RECOMMENDED INSTALLATION PROCEDURES.

**Henry**<sup>®</sup>

999 N. Pacific Coast Highway, Suite 800  
 El Segundo, CA 90245  
 800-486-1278 • www.henry.com

MANUFACTURER GUIDE DETAILS ARE FOR REFERENCE ONLY. HENRY DOES NOT ASSUME RESPONSIBILITY FOR ERRORS OR DEVIATIONS IN DESIGN OR ENGINEERING. PROJECT SPECIFIC VERIFICATION IS RECOMMENDED PRIOR TO INSTALLATION.

**DUNDEQ SYSTEM - PEDESTRIAN/VEHICULAR TRAFFIC COATING**

**NON-MOVING JOINT**

**FULL SEED AND LOCK  
 PEDESTRIAN AND VEHICULAR TRAFFIC COATINGS**

SCALE: N.T.S.

04-10-2020

**DUNDEQ-S1**