

HENRY HIGH TEMPERATURE
ROOFING UNDERLAYMENT

BLUESKIN METAL CLAD

BLUESKIN METAL CLAD
LAP AIR BARRIER 2" ONTO
FLASHING

BLUESKIN METAL CLAD

BLUESKIN METAL CLAD
LAP AIR BARRIER 2" ONTO
FLASHING

BLUESKIN METAL CLAD

BLUESKIN METAL CLAD

BLUESKIN PE200HT
OR BLUESKIN VP160
LAP AIR BARRIER 2" ONTO FLASHING
(INSTALL **BLUESKIN VP160**
WHERE A VAPOR PERMEABLE AIR
BARRIER IS REQUIRED AT PARAPET)

USE DOUBLE SIDED ROOFING TAPE
OR METAL FLASHING AS A
SEPARATOR IF ASPHALT EDGE OF
FLASHING AND ROOFING MEMBRANE
ARE NOT CHEMICALLY COMPATIBLE

OPTIONAL AIR/VAPOR
BARRIER

NOTES:

1. DETAIL SHOWS **BLUESKIN METAL CLAD SELF-ADHERED WATER RESISTIVE AIR BARRIER**. SUBSTRATE SHOWN IS FOR REFERENCE ONLY. ACCEPTABLE SUBSTRATES INCLUDE PLYWOOD, OSB, CONCRETE, CMU, METAL, AND EXTERIOR GRADE SHEATHING.
2. SELF-ADHERED MEMBRANE PRIMER NOT SHOWN FOR CLARITY.
3. OTHER FLASHING OPTIONS INCLUDE: **BLUESKIN BUTYL FLASH, BLUESKIN SA OR BLUESKIN SA LT.**
4. INSTALL **BLUESKIN METAL CLAD** TO ACHIEVE A CONTINUOUS WATER-RESISTIVE BARRIER (WRB). INSULATION AND CLADDING NOT SHOWN FOR CLARITY. REFER TO LOCAL CODE ORDINANCES FOR INSULATION AND VAPOR BARRIER REQUIREMENTS.
5. REFER TO PRODUCT SPECIFIC TECHNICAL DATA SHEET (TDS) AND **BLUESKIN METAL CLAD** GUIDE SPECIFICATION FOR INSTALLATION PROCEDURES.

Henry[®]

999 N. Pacific Coast Highway, Suite 800
El Segundo, CA 90245
800-486-1278 • www.henry.com

MANUFACTURER GUIDE DETAILS ARE FOR REFERENCE ONLY. HENRY DOES NOT ASSUME RESPONSIBILITY FOR ERRORS OR DEVIATIONS IN DESIGN OR ENGINEERING. PROJECT SPECIFIC VERIFICATION IS RECOMMENDED PRIOR TO INSTALLATION.

BLUESKIN METAL CLAD SELF-ADHERED BARRIER

PARAPET TRANSITION

**AIR BARRIER INSTALLED ON FRONT OF WALL
AND AIR BARRIER INSTALLED ON BACK OF WALL**

SCALE: N.T.S.

01-09-2020

MTLCLD-9B