



NOTES:

1. DETAIL SHOWS HENRY **PRODEQ** WATER CONTAINMENT SYSTEM. SUBSTRATE SHOWN IS FOR REFERENCE ONLY. REFER TO PRODUCT SPECIFIC TECHNICAL DATA SHEET FOR AUTHORIZED SUBSTRATES.
2. THE STANDARD PRIMER FOR THE HENRY **PRODEQ** WATER CONTAINMENT SYSTEM IS **HENRY GC EPOXY PRIMER**. OTHER RECOMMENDED PRIMER(S) INCLUDE: **HENRY ST PRIMER** WITH AGGREGATE. REFER TO PRODUCT SPECIFIC DATA SHEET FOR PRODUCT SPECIFIC INFORMATION.
3. DO NOT INSTALL **PRODEQ** WATER CONTAINMENT SYSTEM BEYOND PRIMED SURFACES.
4. REFER TO **PRODEQ** WATER CONTAINMENT SYSTEM GUIDE SPECIFICATION FOR RECOMMENDED INSTALLATION PROCEDURES.



A CARLISLE COMPANY

999 N. Pacific Coast Highway, Suite 800
 El Segundo, CA 90245
 800-486-1278 • www.henry.com

MANUFACTURER GUIDE DETAILS ARE FOR REFERENCE ONLY. HENRY DOES NOT ASSUME RESPONSIBILITY FOR ERRORS OR DEVIATIONS IN DESIGN OR ENGINEERING. PROJECT SPECIFIC VERIFICATION IS RECOMMENDED PRIOR TO INSTALLATION.

PRODEQ SYSTEM - WATER CONTAINMENT SYSTEM

CURB FLASHING

**TYPICAL PRODEQ WATER CONTAINMENT SYSTEM
 UPTURN FLASHING AT CURB**

SCALE: N.T.S.

06-17-2022

PDQ-CS-C4A