



EXTEND **PRO-GRADE® 988** ONTO EXISTING RAIN COLLAR AND PIPE COMPLETELY ENCAPSULATING ALL SURFACES

EXTEND **PRO-GRADE® 988** UNDER SHEET-METAL RAIN COLLAR THOROUGHLY COATING EXPOSED AREAS OF EXISTING ROOFING AND UNDERSIDE OF FLASHING

EXISTING RAIN COLLAR AND FLASHING

PRETREAT CORNER AT PIPE UPTURN AND EXISTING PIPE FLASHING SEAM PRIOR TO COATING INSTALLATION USING ONE OF THE METHODS BELOW: (STAIN BLOCKING PRIMER REQUIRED FOR EXISTING MB/BUR ROOFS -SEE NOTE #2)

- SEALANT (125 WET MILS)
  - **PRO-GRADE® 920**
  - **PRO-GRADE® 923**
  - **PRO-GRADE® 957**
- REINFORCED COATING (32 WET MILS)

**PRO-GRADE® 988**  
(STAIN BLOCKING PRIMER REQUIRED FOR EXISTING MB/BUR ROOFS -SEE NOTE #2)

EXISTING PREVIOUSLY COATED OR NON-COATED ROOFING ASSEMBLY

**NOTES:**

1. DETAIL SHOWS **PRO-GRADE® 988** INSTALLED OVER AN EXISTING PREVIOUSLY COATED OR NON-COATED ROOFING ASSEMBLY. ACCEPTABLE SUBSTRATES INCLUDE GRANULATED OR SMOOTH SURFACED MODIFIED BITUMEN (MB), SMOOTH SURFACED ASPHALT BUILT-UP ROOFING (BUR), AGED EPDM, PVC, HYPALON® OR TPO.
2. INSTALL **PRO-GRADE® 294** STAIN BLOCKING PRIMER ONTO EXISTING MB/BUR ROOF PRIOR TO FLASHING/COATING INSTALLATION (STAIN BLOCKING PRIMER NOT SHOWN FOR CLARITY).
3. COMPLETE ALL DETAILING PRIOR TO INSTALLATION OF ROOF COATING.
4. DECK AND EXISTING ROOFING ASSEMBLY SHOWN ARE FOR REFERENCE ONLY.
5. REFER TO **PRO-GRADE® 988** GUIDE SPECIFICATION, INSTALLATION MANUAL AND/OR APPLICATION GUIDE FOR RECOMMENDED INSTALLATION PROCEDURES.
6. REFER TO **PRO-GRADE® 988** WARRANTY CHART FOR SUBSTRATE SPECIFIC FIELD COATING MINIMUM REQUIREMENTS.

MANUFACTURER GUIDE DETAILS ARE FOR REFERENCE ONLY. HENRY® DOES NOT ASSUME RESPONSIBILITY FOR ERRORS OR DEVIATIONS IN DESIGN OR ENGINEERING. PROJECT SPECIFIC VERIFICATION IS RECOMMENDED PRIOR TO INSTALLATION.

**PRO-GRADE® 988 SILICONE ROOF COATING**

**STACK VENT**

SHEET-METAL STACK VENT (HOT OR COLD)  
ON A MEMBRANE ROOF

SCALE: N.T.S.

06-20-2017

**PG988-6A**

**Henry®**

999 N. Sepulveda Blvd., Suite 800  
El Segundo, CA 90245  
800-486-1278 • www.henry.com