

## NOTES:

- 1. DETAIL SHOWS HENRY **PRODEQ** SYSTEM WATERPROOFING ASSEMBLY. SUBSTRATE SHOWN IS FOR REFERENCE ONLY. REFER TO PRODUCT SPECIFIC TECHNICAL DATA SHEET FOR AUTHORIZED SUBSTRATES.
- THE STANDARD PRIMER FOR THE HENRY PRODEQ SYSTEM IS HENRY ST PRIMER WITH AGGREGATE. OTHER RECOMMENDED PRIMERS INCLUDE: HENRY LV PRIMER, HENRY STXL PRIMER WITH AGGREGATE, PUMADEQ PRIMER 20 WITH AGGREGATE AND HENRY GC EPOXY PRIMER. REFER TO PRODUCT SPECIFIC DATA SHEET FOR PRODUCT SPECIFIC INFORMATION.
- 3. PREPARE AND PRIME VERTICAL SUBSTRATES A MINIMUM 2" (50MM) BEYOND **PRODEQ** SYSTEM APPLICATION IN ACCORDANCE WITH HENRY **PRODEQ** SYSTEM SUBSTRATE PREPARATION GUIDELINES TECH-TALK BULLETIN.
- 4. DO NOT INSTALL **PRODEQ** SYSTEM BEYOND PRIMED SURFACES.
- HENRY OFFERS PAVERS, RIGID INSULATION, AND/OR PREFABRICATED DRAINAGE COMPOSITES AS A SINGLE SOURCE WARRANTY OPTION PER PROJECT SPECIFIC REQUIREMENTS (NOT SHOWN FOR CLARITY). CONTACT HENRY FOR SYSTEM CONFIGURATIONS AND WARRANTY OPTIONS.
- 6. REFER TO PRODEQ SYSTEM GUIDE SPECIFICATION FOR RECOMMENDED INSTALLATION PROCEDURES.



999 N. Pacific Coast Highway, Suite 800

El Segundo, CA 90245

800-486-1278 • www.henry.com

MANUFACTURER GUIDE DETAILS ARE FOR REFERENCE ONLY. HENRY DOES NOT ASSUME RESPONSIBILITY FOR ERRORS OR DEVIATIONS IN DESIGN OR ENGINEERING. PROJECT SPECIFIC VERIFICATION IS RECOMMENDED PRIOR TO INSTALLATION.

## PRODEQ SYSTEM - WATERPROOFING ASSEMBLY

## **SCUPPER**

TYPICAL PRODEQ SYSTEM
THRU-WALL SCUPPER FLASHING

SCALE: N.T.S.

06-17-2022

PRODEQ-D3A