

NOTES:

- 1. DETAIL SHOWS HENRY VEGETATIVE ROOFING WITH **PUMADEQ** SYSTEM WATERPROOFING ASSEMBLY WITH A REINFORCED FIELD MEMBRANE. SUBSTRATE SHOWN IS FOR REFERENCE ONLY. REFER TO PRODUCT SPECIFIC TECHNICAL DATA SHEET FOR AUTHORIZED SUBSTRATES.
- 2. THIS DETAIL IS INTENDED FOR NON-MOVING SUBSTRATE GAPS. REFER TO EXPANSION JOINT DETAILS FOR AREAS WHERE BUILDING MOVEMENT IS ANTICIPATED.
- 3. REMOVE EXCESS PRIMER FROM GAP PRIOR TO APPLYING PUMADEQ FLEX 30SL.
- 4. DO NOT INSTALL PUMADEQ SYSTEM BEYOND PRIMED SURFACES.
- 5. DEPTH OF GROWING MEDIA MAY VARY DEPENDING ON PROJECT SPECIFIC REQUIREMENTS.
- 6. DETAIL IS FOR REFERENCE ONLY. REFER TO DESIGN PROFESSIONAL TO VERIFY WIND UPLIFT REQUIREMENTS.
- 7. REFER TO THE **PUMADEQ** SYSTEM GUIDE SPECIFICATION AND WATERPROOFING DETAILS FOR RECOMMENDED INSTALLATION PROCEDURES.



El Segundo, CA 90245 800-486-1278 • www.henry.com MANUFACTURER GUIDE DETAILS ARE FOR REFERENCE ONLY. HENRY DOES NOT ASSUME RESPONSIBILITY FOR ERRORS OR DEVIATIONS IN DESIGN OR ENGINEERING. PROJECT SPECIFIC VERIFICATION IS RECOMMENDED PRIOR TO INSTALLATION.

VEGETATIVE ROOFING - PUMADEQ SYSTEM

PRECAST CONCRETE PLANK/PANEL JOINT TREATMENT

NON-MOVING JOINT REINFORCED FIELD MEMBRANE (CSP 3-5)

SCALE: N.T.S. 06-01-2020

VR-PUMA-R2E