

## NOTES:

- DETAIL SHOWS HENRY VEGETATIVE ROOFING WITH **PUMADEQ** SYSTEM WATERPROOFING ASSEMBLY WITH AN UNREINFORCED FIELD MEMBRANE. SUBSTRATE SHOWN IS FOR REFERENCE ONLY. REFER TO PRODUCT SPECIFIC TECHNICAL DATA SHEET FOR AUTHORIZED SUBSTRATES.
- SURFACE PROFILES MUST MEET ICRI CSP 3-4. IF CSP 5. REFER TO REINFORCED PUMADEQ SYSTEM DETAILS.
- 3. REMOVE EXCESS PRIMER FROM SUBSTRATE DEFICIENCY PRIOR TO APPLYING **PUMADEQ FLEX 32TX** OR **PUMADEQ PRM**.
- 4. DO NOT INSTALL **PUMADEQ** SYSTEM OVER SUBSTRATES/AREAS THAT EXCEED MAXIMUM MOISTURE ALLOWANCES. VERIFY DEFICIENCIES DO NOT HAVE PERCOLATING MOISTURE. REFER TO **PUMADEQ** SYSTEM MOISTURE TEST METHODS TECH-TALK BULLETIN FOR FURTHER INFORMATION.
- 5. DO NOT INSTALL PUMADEQ SYSTEM BEYOND PRIMED SURFACES.
- 6. DEPTH OF GROWING MEDIA MAY VARY DEPENDING ON PROJECT SPECIFIC REQUIREMENTS.
- 7. DETAIL IS FOR REFERENCE ONLY. REFER TO DESIGN PROFESSIONAL TO VERIFY WIND UPLIFT REQUIREMENTS.
- 8. REFER TO THE **PUMADEQ** SYSTEM GUIDE SPECIFICATION AND WATERPROOFING DETAILS FOR RECOMMENDED INSTALLATION PROCEDURES.



El Segundo, CA 90245

800-486-1278 • www.henry.com

MANUFACTURER GUIDE DETAILS ARE FOR REFERENCE ONLY. HENRY DOES NOT ASSUME RESPONSIBILITY FOR ERRORS OR DEVIATIONS IN DESIGN OR ENGINEERING. PROJECT SPECIFIC VERIFICATION IS RECOMMENDED PRIOR TO INSTALLATION.

## VEGETATIVE ROOFING - PUMADEQ SYSTEM

## SUBSTRATE DEFICIENCY

UNREINFORCED FIELD MEMBRANE (CSP 3-4) SUBSTRATE DEFICIENCY

SCALE: N.T.S. 06-01-2020

**VR-PUMA-U2D**