

Henry® commercial air barrier systems selection chart

	Fluid applied				Self-adhered sheet				Flashings				Sealants		Primers						
	Air-Bloc All Weather STPE ⁵	Air-Bloc® 16MR	Air-Bloc® 17MR	Air-Bloc® 21	Blueskin® VP160	Blueskin® SA	Blueskin® SA LT	Blueskin® Metal Clad®	Air-Bloc LT	Blueskin® Metal Clad® LT	Blueskin® Butyl Flash	Blueskin® TWF	Blueskin® SA	Blueskin® SA LT	Blueskin® Metal Clad®	Henry® 212 All Purpose Crystal Clear Sealant	Henry® 925 BES Sealant	Blueskin® Adhesive	Blueskin® LVC Adhesive	Aquatac™ Spray Prep Adhesive	Aquatac™ Primer
Vapor permeable	•		•		•					•								•	•	•	•
Vapor impermeable		•		•		•	•	•	•		•	•	•	•	•	•	•				
Permanent UV exposure <i>Under open joint cladding</i>	•							•	•					•	•						
Low application temperature <i>Lower than 40 °F (4 °C)</i>	•	•	•	•	• ¹	• ¹	•	•	•	•	•	•	• ¹	•	•	•	•	•	•	•	•
Low VOC ²	•	•	•		n/a	n/a	n/a	n/a	n/a	•	n/a	n/a	n/a	n/a	n/a		•		•		•
Self-gasketing	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•				
Mold resistant	•	•	•		n/a	n/a	n/a	n/a	n/a	•	n/a	n/a	n/a	n/a	n/a						
NFPA 285 compliance	§	•	§	•	•	•	•	§	§	n/a ⁴	n/a ⁴	n/a ⁴	n/a ⁴	n/a ⁴	n/a ⁴	n/a ⁴	n/a ⁴	n/a ⁴	n/a ⁴	n/a ⁴	n/a ⁴
Declare label	•	•	•		•	•	•	•	•			•	•	•	•						
ABAA evaluated	•	•	•		•																

§ Meets 2015 IBC 1403.5 exception #2 1. Primer required 2. VOC regulations do not apply to articles such as sheet applied membranes and flashings. VOCs are only measured in certain liquid products. 3. Can only be used with Blueskin VP160
 4. Flashing of fenestration products and weather resistive barrier flashing and accessories at other locations shall not be considered part of the weather resistive barrier for NFPA 285 compliance in accordance with the International Building Code.
 5. Passes AAMA 714-19. Can also be used as a liquid flashing when Air-Bloc All Weather STPE is the primary air barrier membrane. See Installation Manual and Technical Data Sheet for application details.



Air permeance and durability:
 Low air permeance per ASTM E2178 and ASTM E2357. Meet CAN/ULC S741 and S742 air permeance and long-term durability standards.



Self-gasketing:
 Meet ASTM D1970 and AAMA 711 for sealing around fasteners, eliminating water penetration even after the exterior facade is installed.



Wall assembly fire test:
 One of the industry's broadest lines of commercial air barriers that pass as part of various wall assemblies per NFPA 285. Air-Bloc All Weather STPE, Air-Bloc 17MR and Blueskin Metal Clad meet 2015 IBC 1403.5 exception #2.



Sustainable and environmental design benefits:
 Contribute to sustainable design, energy efficiency and LEED credits, by utilizing durable, low-VOC air barriers. Health Product Declarations and Red List status information are available for transparency.

Consult updated Technical Data Sheet for most recent information

Henry, Blueskin, Air-Bloc, Metal Clad and Building Envelope Systems are registered trademarks of the Henry Company.

Ask us today about other Henry® solutions that help manage the flow of water, air, vapor and energy.

Building Envelope Systems®
 Roofing | Air Barrier | Waterproofing

