

Henry® commercial air barrier systems selection chart

	Primary air barrier membranes										Flashings				Sealants			Primers	
	Fluid applied						Self-adhered sheet†				Air-Bloc® LF	Blueskin® Butyl Flash	Blueskin® TWF	212 All Purpose Crystal Clear	Blueskin® Sealant	Blueskin® Adhesive	Blueskin® LVC Adhesive	Blueskin® Spray Prep Adhesive	Aquatac™ Primer
	Air-Bloc® 16MR	Air-Bloc® 17MR	Air-Bloc® 21	Air-Bloc® 31MR	Air-Bloc® 32MR	Air-Bloc® 33MR	Blueskin® VP160	Blueskin® SA	Blueskin® SA LT	Metal Clad®									
Vapor permeable		•		•		•	•					•				•	•	•	•
Vapor impermeable	•		•		•			•	•	•			•	•	•				
UV stable <i>For permanent exposure</i>												•		•	•				
Low application temperature <i>Lower than 40 °F (5 °C)</i>	•	•	•				•*		•*							•	•	•	
Low VOC** <i>100 g limit</i>	•	•		•	•	•	n/a	n/a	n/a	n/a		•	n/a	n/a		•			•
Self-gasketing	•	•	•	•	•	•	•	•	•	•		•	•	•	•				
Mold resistant	•	•		•	•	•						•							
NFPA 285 compliance	All Henry® commercial air barriers are compliant in NFPA 285 wall assemblies.																		

* Primer required

** VOC regulations do not apply to articles such as sheet applied membranes and flashings. VOCs are only measured in certain liquid products.

† Available in a variety of roll widths to also accommodate flashing applications

Air permeance and durability:
Low air permeance per ASTM E2178 and ASTM E2357. Meet CAN/ULC S741 and S742 air permeance and long-term durability standards.

Self-gasketing:
Meet ASTM D1970 and AAMA 711 for sealing around fasteners, eliminating water penetration even after the exterior facade is installed.

Wall assembly fire test:
One of the industry's broadest lines of commercial air barriers that pass as part of various wall assemblies per NFPA 285.

Sustainable and environmental design benefits:
Contribute to sustainable design, energy efficiency and LEED credits, by utilizing durable, low-VOC air barriers. Health Product Declarations and Red List status information are available for transparency.

Consult updated **Technical Data Sheet** for most recent information

Henry, Blueskin, Air-Bloc and Metal Clad are registered trademarks of the Henry Company.

Ask us today about other Henry® solutions that help manage the flow of water, air, vapor and energy.

Building Envelope Systems®
Roofing | Air Barrier | Waterproofing