



Henry® Roof Restoration Product Catalog

Made Especially for the Contractor



Roof Coatings | Sealants | Primers | Mastics & Roof Cements | Repair & Reinforcement Fabrics | Spray Foam



Protecting roofs and reputations since 1933

For almost a century, Henry has provided professional roofing contractors with proven solutions. We know water intrusion impacts lives every day, and your reputation is on the line with every job and every product you install. We are here for you, to help you select the right products and systems to mitigate water intrusion and deliver solutions with confidence.

The Henry Roof Restoration product line was developed specifically for professional roofing contractors, and is backed by industry-leading warranties. When you choose Henry you can rest assured that you're receiving superior performing solutions that will protect your projects and your reputation.

Roof Coatings

Silicone Roof Coatings

Henry Pro-Grade 988 Silicone White Roof Coating

- Dirt Pick-Up Resistance (DPUR) formula – Stays whiter and brighter longer
- Rain safe in 15 minutes
- Permanent ponding water resistance
- High solids content, one coat application
- Superior UV resistance and reflectivity
- Helps lower roof and interior temperatures providing energy savings
- Low odor and VOC compliant in all jurisdictions
- Proven waterproofing performance per ASTM D7281
- Helps extend the existing roof membrane life cycle
- Restoration System installation qualifies for up to 20-year Material, Labor & Workmanship Henry Gold Seal Warranty

Coverage: 1.5 gallons/square

Sizes available: 4.75 gallon pail and 55 gallon drum

Colors: White, gray and tan



Henry Pro-Grade 988 Premium & Custom Color Silicone Roof Coating

- Permanent ponding water resistance
- Low odor and VOC compliant in all jurisdictions
- High solids content, one-coat application
- Excellent adhesion to many substrates
- Restoration System installation qualifies for up to 20-year Material, Labor & Workmanship Henry Gold Seal Warranty

Coverage: 1.5 gallons/square

Sizes available: 4.75 gallon pail and 55 gallon drum

Minimum Order Quantity: 3,300 Gallons for Custom Color

Colors: Almond, brick red, brown, charcoal, terra cotta, safety yellow and custom



Acrylic Roof Coatings

Henry Pro-Grade 280 Elastomeric White Roof Coating

- Premium water-based 100% acrylic latex coating
- Highly resistant to disbonding, chalking, mildew, fungi, discoloration
- Helps extend the existing roof membrane life cycle
- Meets or exceeds ASTM D6083 - Standard Specification for Liquid Applied Acrylic Coating Used in Roofing
- Restoration System installation qualifies for up to 12-Year Material, Labor & Workmanship Henry Gold Seal Warranty

Coverage: 3.0 gallons/square to be applied in two coats at 1.5 gallons/square

Sizes available: 4.75 gallon pail, 55 gallon drum and 275 gallon tote

Color: White



Spray Polyurethane Foam

PremiR+® EVO™

- Provides a fully adhered, monolithic, sustainable air barrier and thermal insulation
- Superior yield reduces cost and amount of material required
- Enhanced wind uplift resistance for a fully adhered roof system
- Yields a smooth surface, reducing the need for extra coating
- Self-flashing, seamless application
- Does not contain any HFCs or HCFCs

Sizes available: 55 gallon drum



Roof Coatings

Aluminum Roof Coatings

Henry Pro-Grade 599 Rubberized Aluminum Roof Coating - Solvent-based

- One-coat application – no primer required
- Excellent flexibility
- Helps extend the existing roof membrane life cycle
- Helps lower interior temperatures as well as energy costs
- Restoration System installation qualifies for up to 12-Year Material, Labor & Workmanship Henry Gold Seal Warranty

Coverage: 1.5 - 2.5 gallons/square

Sizes available: 4.75 gallon pail and 50 gallon drum



Henry Pro-Grade 586 Fibered Aluminum Roof Coating - Solvent-based

- Resists moisture intrusion and levels irregularities in asphaltic roof surfaces
- Helps extend the existing roof membrane life cycle
- Low odor and VOC compliant in all jurisdictions
- Restoration System installation qualifies for up to a 12-Year Material, Labor & Workmanship Henry Gold Seal Warranty

Coverage: 1.5 - 2.5 gallons/square

Sizes available: 4.75 gallon pail and 50 gallon drum



Henry Pro-Grade 588 Aluminum WB Roof Coating - Water-based

- Resists moisture intrusion and levels irregularities in asphaltic roof surfaces
- Helps extend the existing roof membrane life cycle
- Low odor and VOC compliant in all jurisdictions
- Restoration System installation qualifies for up to a 12-Year Material, Labor & Workmanship Henry Gold Seal Warranty

Coverage: 1.5 gallons/square

Sizes available: 4.75 gallon pail, 50 gallon drum and 250 gallon tote



Asphalt Roof Coatings

Henry Pro-Grade 197 Asphalt Emulsion

- Resists moisture intrusion and levels irregularities in asphaltic roof surfaces
- Helps extend the existing roof membrane life cycle
- Low odor and VOC compliant in all jurisdictions
- Restoration System installation qualifies for up to a 12-Year Material, Labor & Workmanship Henry Gold Seal Warranty

Coverage: 3.0 gallons/square

Sizes available: 4.75 gallon pail, 55 gallon drum and 275 gallon tote



Sealants & Accessories

Silicone Sealants

Henry Pro-Grade 957 Silicone Fibered Roof Sealer

- Reinforced with fibers
- Excellent repair material for many roofing substrates
- Seals flashings, fasteners, seams and drains
- Easily applied by trowel up to 1/2" thick on vertical or horizontal applications

Application Rate	Coverage per Gallon
1/16" thickness	24 sq. ft./gal.
1/8" wide	12 sq. ft./gal.
1/4" wide	6 sq. ft./gal.

Sizes available: 2 gallon pail

Color: White



Henry Pro-Grade 923 Butter Grade Silicone Roof Sealer

- Excellent repair material for many roofing substrates
- Seals flashings, fasteners, seams and drains
- Easily applied by brush or trowel up to 1/4" thick on vertical or horizontal applications

Application Rate	Coverage per Gallon
1/16" thickness	24 sq. ft./gal.
1/8" wide	12 sq. ft./gal.
1/4" wide	6 sq. ft./gal.

Sizes available: 2 gallon pail

Color: White



Henry Pro-Grade 920 Silicone Roof Sealant

- Seals roof membrane seams, concrete cracks, flashing, drains and damaged areas on most roof substrates
- No hardening, chalking, crazing, cracking or reverting
- Wide temperature performance range: -40 °F to 200 °F
- 100% silicone moisture-cure technology

Sizes available: 10.1 oz cartridge

Color: White



Henry Pro-Grade 928 Pitch Pocket & Self-Leveling Roof Sealer

- Encapsulates and seals fasteners on metal roofs
- Forms a watertight, non-shrinking seal for penetrations in metal pitch pocket flashings

Coverage: 150 - 200 fasteners/cartridge at 1/2" diameter

Sizes available: 10.1 oz cartridge

Color: Black



Acrylic Sealants & Accessories

Henry 295 Metal Seam Sealer - Solvent-based

- Rubber-based, mastic-grade, elastomeric sealant designed to seal critical fasteners and lap seams on metal roofing
- Can be applied with a bulk cartridge applicator
- May be coated with either an acrylic or solvent-based elastomeric reflective coating, or an asphalt-aluminum reflective coating
- Not for use in VOC regulated areas

Application Rate	Coverage per Gallon
1/2" bead	75 linear ft./gal.
1/4" thickness	4" wide - 20 linear ft./gal.
6" wide	13 linear ft./gal.
12" wide	6.5 linear ft./gal.

Sizes available: 5 gallon pail

Color: White



Henry 289 White Roofing Sealant - Water-based

- Elastomeric acrylic patching compound
- Applies to dry or damp (not wet) surfaces
- Doesn't "bleed through" reflective coatings
- Skins over quickly - no delays

Coverage: 12 1/2 sq. ft. per gallon applied 1/8" thick.

Sizes available: 10.1 oz. cartridge, 1 gallon, 3.5 gallon

Color: White



MIAMI-DADE COUNTY
APPROVED

Primers

Henry Pro-Grade 294 Base Coat & Sealer

- Stain-blocking sealer for use on asphaltic surfaces prior to silicone roof coating systems
- Gray base coat for use in water-based white roof coating systems
- Highly resistant to disbonding

Coverage: 1.5 gallons/square when used as a base coat prior to application of Henry Pro-Grade 280
1.0 gallons/square when used as a stain blocker prior to application of Henry Pro-Grade 988

Sizes available: 4.75 gallon pail, 55 gallon drum and 275 gallon tote

Color: Gray



Henry Pro-Grade 941 Primer

- One-coat adhesion promoter designed to enhance the bond strength of silicone coatings to roof surfaces
- Quick drying

Coverage: 500 sq. ft./gallon

Sizes available: 1 gallon can



Repair & Reinforcement Fabrics

Henry 181 Black Asphalt Saturated Glass Fabric

- Woven, open-mesh fiberglass
- 20 x 10 thread count
- ASTM D1668

Sizes available: 4 in. x 150 ft., 6 in. x 150 ft., 36 in. x 150 ft.



Henry 296 ElastoTape™ Repair Fabric

- 100% spunbonded, non-woven polyester mat
- High tensile strength
- Puncture resistant
- Excellent reinforcement fabric for roofing and waterproofing applications

Sizes available: 4 in. x 150 ft.



Henry 183 Yellow Resin Coated Glass Fabric

- Yellow resin coating minimizes distortion and aids in quality workmanship
- Compatible with asphalt cements and coatings, emulsions, solvent-based and hot-melt products
- Woven, open-mesh fiberglass
- 20 x 10 thread count
- ASTM D1668

Sizes available: 4 in. x 150 ft., 6 in. x 150 ft., 36 in. x 150 ft.



Henry 195 Polyester Fabric

- Contains soft-finish polyester
- Provides an ideal reinforcing component in cold process roofing and repair
- Conforms readily to irregular surfaces

Sizes available: 6 in. x 300 ft., 12 in. x 300 ft., 40 in. x 324 ft., 6 ft. x 324 ft.



Mastics & Roof Cements

Henry Pro-Grade 167 Extreme Rubberized Flashing Cement

- Contains UV inhibitors and SEBS rubber for durability
- Suitable for extreme weather conditions
- Superior elasticity and flexibility; ideal for control joints and seams or anywhere else movement is expected
- Installation temperature range (ambient): -20 °F to 140 °F
- 100% underwater adhesion per ASTM D3409
- Meets or exceeds ASTM D4586, Standard Specification for Asphalt Roof Cement

Coverage: 12 sq. ft. per gallon applied 1/8" thick
6 sq. ft. per gallon for 3-course application

Sizes available: 1 gallon can and 3 gallon pail

Color: Black



MIAMI-DADE COUNTY
APPROVED

Henry Pro-Grade 155 Flashing Cement

- Contains SBS rubber for flexibility and elasticity
- Will not sag/slip even at high roof temperatures
- Low temperature and summer grades
- Meets or exceeds ASTM D4586, Standard Specification for Asphalt Roof Cement

Coverage: 12 sq. ft. per gallon applied 1/8" thick
30 sq. ft. per 4.75 gallon pail for 3-course application

Sizes available: 4.75 gallon pail

Color: Black



MIAMI-DADE COUNTY
APPROVED

Henry Pro-Grade 163 Emergency Leak Repair Sealant

- Modified with SBS rubber for improved flexibility and durability
- Tenacious adhesion even when applied underwater
- Spreads easily, even in cold weather
- Installation temperature range (ambient): 0 °F to 120 °F
- 100% underwater adhesion per ASTM D3409
- Meets or exceeds ASTM D4586, Standard Specification for Asphalt Roof Cement

Coverage: 12 sq. ft. per gallon applied 1/8" thick
6 sq. ft. per gallon for 3-course application

Sizes available: 10.1 oz cartridge, 1 gallon can and 3 gallon pail

Color: Black



MIAMI-DADE COUNTY
APPROVED

Henry Pro-Grade 151 Plastic Cement

- Smooth, easy-to-use, trowel application
- Contains 100% recycled fibers for added strength and durability
- Excellent adhesion to many common roof surfaces
- Low temperature and summer grades
- Meets or exceeds ASTM D4586, Standard Specification for Asphalt Roof Cement

Coverage: 12 sq. ft. per gallon applied 1/8" thick
30 sq. ft. per 5 gallon pail for 3-course application

Sizes available: 4.75 gallon pail

Color: Black



MIAMI-DADE COUNTY
APPROVED

Henry Pro-Grade 161 All Weather Flashing Cement

- Appropriate for setting and repairing SBS Modified Bitumen flashings
- Modified with SBS rubber for improved flexibility and durability
- Will not curl or chase the trowel when applied underwater
- Low-temperature and summer-grade formulations allow for an installation temperature range (ambient) of 20 °F to 120 °F
- 100% underwater adhesion per ASTM D3409
- Meets or exceeds ASTM D4586, Standard Specification for Asphalt Roof Cement

Coverage: 12 sq. ft. per gallon applied 1/8" thick
30 sq. ft. per 4.75 5 gallon pail for 3-course application

Sizes available: 4.75 gallon pail

Color: Black



MIAMI-DADE COUNTY
APPROVED

Henry®

Building Envelope Systems®

Roofing | Air Barrier | Waterproofing

Ask us today about other Henry® solutions that help manage the flow of water, air, vapor and energy.

For more information, visit www.henry.com/roof-restoration-systems or for technical assistance call us at 800-486-1278.

Henry, Pro-Grade and #1 Choice of Professionals are registered trademarks of Henry Company.

1-800-486-1278
www.henry.com

© 2023 Henry Company. All rights reserved.
Printed in U.S.A. 142.3US.E005 (06/23)