



A step 1 component of the Henry® 1-2-3 Moisture Control System™



Henry® Two-Ply Hydro Tex™ Drainable Weather-Resistive Barrier




Two superior products in a single roll

Henry® Two-Ply Hydro Tex™ combines our **Super Jumbo Tex® 60 Minute** building paper with our **WeatherSmart® Drainable** drainage wrap, bringing these two proven layers of protection together in one roll. **Hydro Tex** delivers much higher drainage performance than standard dual-ply weather-resistive barriers and saves the labor cost of wrapping the building twice with two separate products.

Hydro Tex is designed to protect homes and commercial buildings from the internal wall damage caused by water intrusion and is backed by an industry-leading 15-year warranty that covers defective product and provides materials PLUS labor for warranted repairs when used as part of the Henry® 1-2-3 Moisture Control System™.

Features and benefits



More than 95% drainage efficiency



Excellent balance between water resistance and permeability



Crush-resistant drainable pattern



Labor saving two-ply protection in one pass

Performance standards you can trust

Hydro Tex is a scientifically advanced barrier combined with a professional Grade “D” building paper, designed for use within a variety of exterior wall assemblies. It provides excellent protection from wall damage due to water intrusion and condensation.

Physical/performance property	Typical value	Test method
Moisture vapor transmission	49.8 g/sm/day (7.6 perms)	ASTM E96
Drainage efficiency	> 95% Pass	ASTM E2273
Water resistance	>120 minutes	ASTM D779
Tensile strength	MD - 80 lb./inch CD - 30 lb./inch	ASTM D828

**Hydro Tex is tested in accordance with ASTM International procedures. The values shown are typical values obtained in these tests.*

Product characteristics

Composition	Asphalt-saturated kraft Grade “D” breather type sheathing paper and spunbond polypropylene breathable fabric coated with a non-perforated breathable barrier layer
Roll size	40" x 48.6 lineal feet.
Weight	7.4 lbs per 100 sq. ft.

Product approvals, certifications and specifications

Complies with the International Code Council Evaluation Services Acceptance Criteria for Water Resistive Barriers (AC 38)
Complies as an alternative to the water-resistive barrier specified in Section 1404.2 of the International Building Code® (IBC)
Complies as an alternative to the weather-resistant sheathing papers specified in Section R703.2 of the International Residential Building Code® (IRC)
Exceeds Federal Specification UU-B-790a, Type 1, Grade “D”, Style 2
Exceeds ASTM E2556 Type II performance requirements
ICC Evaluation Service Report 1027
ASTM D779 – Standard Test Method for Water Resistance of Paper, Paperboard, and Other Sheet Materials by the Dry Indicator Method
ASTM D828 – Tensile Properties of Paper and Paperboard Using Constant-Rate-of-Elongation Apparatus
ASTM E96 – Standard Test Method for Water Vapor Transmission of Materials
ASTM E2273 – Standard Test Method for Determining the Drainage Efficiency of Exterior Insulation and Finish Systems (EIFS) Clad Wall Assemblies
ASTM E2556 – Standard Specification for Vapor Flexible Sheet Water-Resistive Barriers Intended for Mechanical Attachment

Limitations: Product should be covered as soon as possible. Inspect product to insure it is free of any protrusions or damage which may detract from the weather-resistive barrier integrity. Holes, tears or punctures should be sealed with Moistop® Sealant or Henry Sheathing Tape. This product is not recommended for horizontal, roofing or below grade applications.

Installation: Hydro Tex should be installed in accordance with the local applicable building code. Weather-resistive barriers should be applied horizontally, with the upper layers overlapping the lower layer by a minimum of 2" (3" is recommended), and all vertical joints should be lapped a minimum of 6". Ensure that the Super Jumbo Tex side (black layer) is installed to the outside. Do not tape horizontal or vertical seams.

Availability: Henry products are distributed nationwide. For product information and pricing, please call a Henry distributor near you. If you need assistance locating a participating distributor, please call our Customer Service Department at 1-800-773-4777.

Henry Product Warranty Information: This product may be eligible for the 15-year Henry 1-2-3 Moisture Control System Warranty when used in conjunction with other products. See <https://us.henry.com/warranty> for details.

We, the manufacturer, warrant only that this product is free of defects, since many factors which affect the results obtained from this product – such as weather, workmanship, equipment utilized, and prior condition of the substrate – are all beyond our control. We will replace at no charge any product proved to have a material defect within 12-months of purchase, provided it has been applied in accordance with our written directions for uses we recommend as suitable for this product. Proof of purchase must be provided.

DISCLAIMER OF WARRANTIES AND LIMITATION OF LIABILITY: THIS LIMITED WARRANTY IS IN LIEU OF ANY OTHER WARRANTIES, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. NO ONE, INCLUDING THE MANUFACTURER, SHALL HAVE ANY LIABILITY OF ANY KIND BEYOND PRODUCT REPLACEMENT, INCLUDING FOR NEGLIGENCE OR FOR DIRECT, CONSEQUENTIAL, EXEMPLARY OR INCIDENTAL DAMAGES, RESULTING FROM ANY MISUSE, DEFECTS OR DELAYS CAUSED BY REPLACEMENT OR OTHERWISE. IF PURCHASER DOES NOT ACCEPT THESE TERMS, PURCHASER MAY RETURN WITHIN 30-DAYS OF PURCHASE ALL UNOPENED CONTAINERS OR PACKAGES OF PRODUCT PURCHASED FOR A FULL REFUND. RETENTION OF PRODUCT BEYOND 30-DAYS, OR USE OF PRODUCT SHALL CONSTITUTE ACCEPTANCE OF THESE TERMS, CONDITIONS, AND DISCLAIMERS. THIS LIMITED WARRANTY AND LIABILITY DISCLAIMER PROVIDES THE PURCHASER'S EXCLUSIVE REMEDY FOR ANYTHING RELATING TO THE PRODUCT.

To the extent that any part of this LIMITED PRODUCT WARRANTY AND LIABILITY DISCLAIMER is determined unenforceable under the law of the place of purchase of the product, that part is severed and the remainder of these terms remain in full force and effect. To the extent permitted by law, the duration of any implied warranties is limited to the duration of Henry's express warranty.

This warranty language supersedes any language found elsewhere, including product labels, sell sheets and/or technical documents.



Featuring a range of compatible weather barriers, flashings and sealants, the Henry® 1-2-3 Moisture Control System™ makes it easier than ever to build with confidence.

Henry, Building Envelope Systems, HydroTex, Moistop, WeatherSmart and Super Jumbo Tex are registered trademarks of the Henry Company.

Henry®

Building Envelope Systems®
Wall & Window | Roof | Foundation

Ask us today about other Henry® solutions that help manage the flow of water, air, vapor and energy.