

Henry® Prodeq™ Waterproofing System Selection Chart

The Henry Prodeg System is comprehensive waterproofing system for plaza decks, roofs, split slabs, terraces, as well as water containment and UV exposure. It provides superior waterproofing protection with a variety of overburden solutions, allowing for both design and budget flexibility.

Use the selection chart below to choose which Henry Prodeg System is right for your waterproofing application.


Products		Plaza Deck System	UV Exposed System	Water Containment System
Primer	Henry ST Primer 20	•	•	•
	Henry GC Epoxy Primer ¹	•	•	•
	Henry LV Primer	•	•	•
Membrane	Henry Prodeq [™] FX400	•		•
	Henry Prodeq [™] FX425		•	
	Henry Prodeq [™] FX600			•
	Henry Prodeq [™] FX650²			•
Wearcoat	Henry GP Wearcoat	Optional ³		
Aggregate	Sand sieve size 20-30 or approved by Henry®	As required³		

¹ Henry GC Epoxy Primer may be used in lieu of Henry ST Primer or Henry LV Primer on green or damp concrete surfaces


Plaza Deck System

nsulation (Optional) Henry GP Wearcoat Henry Prodea FX400 Henry ST Primer

Water Containment System



UV Exposed System



Henry, Prodeq and Building Envelope Systems are registered trademarks of Henry Company

Ask us today about other Henry® solutions that help manage the flow of water, air, vapor and energy.

Building Envelope Systems® Roofing | Air Barrier | Waterproofing

² When NSF 61 Potable Water Certification is required

³ Henry GP Wearcoat and Aggregate may be required when the Prodeg Plaza Deck System is expected to be left exposed and trafficked for long periods of time prior to being covered with overburden