



A step 1 component of the Henry® 1-2-3 Moisture Control System™ for 15 years of warranty coverage



Henry® Residential & Light Commercial Weather Barrier Systems

	Self Adhered					Mechanically Fastened						
	Blueskin® VP100	WeatherSmart® Commercial	WeatherSmart® Drainable	WeatherSmart® D	WeatherSmart®	WeatherSmart® Rainscreen	HydroTex™	Two-Ply Super Jumbo Tex® 60 min	Super Jumbo Tex® 60 Min	Two-Ply Jumbo Tex®	Jumbo Tex®	PlyDry®
Vapor Permeable	•	•	•	•	•	•	•	•	•	•	•	•
Drainage Efficiency, >90%	•		•	•		•	•					
Water Vapor Transmission	33 perms	14 perms	15 perms	23.5 perms	8 perms		7.6 perms	11 perms	11 perms	10 perms	10 perms	8.1 perms
Water Resistance	>60 minutes	>60 minutes	>60 minutes	>60 minutes	>60 minutes		>120 minutes	150 minutes	60 minutes	110 minutes	20 minutes	>30 minutes
UV Exposure	150 days	365 days	180 days	180 days	180 days		30 days*	30 days*	30 days*	30 days*	30 days*	120 days
Minimum Application Temperature	20° F	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a
Self-gasketing	•											
NFPA 285 Compliance		•	•	•	•	•	•	•	•			
Red List Free	•	•	•	•	•	•	•	•	•	•	•	•
Henry 1-2-3 Moisture Control System	•	•	•	•	•	•	•	•	•	•	•	•

*Products should be covered as soon as possible. Exposure should not exceed 30 days.



Air & Vapor Permeance:
Low air permeance per ASTM E2178 and water vapor transmission per ASTM E 96.



Self-gasketing:
Meet ASTM D1970 and AAMA 711 for sealing around fasteners, eliminating water penetration even after the exterior facade is installed.



Wall Assembly Fire Test:
Mechanically fastened weather-resistive barriers that pass as part of various wall assemblies per NFPA 285.

Consult updated **Technical Data Sheet** for most recent information

Henry, Blueskin, WeatherSmart, Jumbo Tex and Ply Dry are registered trademarks of the Henry Company.

Ask us today about other Henry® solutions that help manage the flow of water, air, vapor and energy.

Building Envelope Systems®
Roofing | Air Barrier | Waterproofing

productsupport@henry.com | 1-800-486-1278
www.henry.com

© 2022 Henry Company All rights reserved.
Printed in U.S.A. 215.3US.E586 (09/22)